

32 AMP SINGLE SCREW INS.CONN PK100

Part Number: C32A1



Features

- Heavy-duty insulated screw connectors for a max. of 2 x 6mm² cables
- Available in one or one with wire protection or two screw formats
- Clear polycarbonate housing so termination can be visually checked
- Rated for normal 240/415V applications, 32 Amps
- Polycarbonate housing, brass body and steel screw

Insulated Single Screw Connector 32 Amp

Heavy duty insulated screw connectors accommodate a maximum of 2 x 6mm² cables, and are made in one and two screw formats, the two screw being for the earth.

Insulated Screw Connector Features

- Clear plastic housing so that termination can be visually checked
- Soft plastic housing with no sharp edges for user comfort
- Nominal 32A rating, dependant on conductor loading
- Rated for normal 240/415V applications
- Supplied in handy screw top jars

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

Applications

Insulated screw connectors are typically used by electricians, in junction boxes for general connections, to connect light fittings, and virtually anywhere in general purpose wiring.

Technical Data

Material Body: PVC

Connections: Brass

Nominal ratings

Voltage: 240/415V

Amperage: 32A

Additional Information

Certificate of Standards Conformity

[Download Certificate of Standards Conformity](#)

ROHS

[Download ROHS](#)

Datasheet

[Download Datasheet](#)

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.