

AUTO IGNITION BUTANE POWERED PRO TORCH

Part Number: GT1400



Features

- Ideal for industrial applications
- Torch runs on normal cigarette lighter fuel
- Use for brazing, soldering, plumbing, industrial maintenance
- Nominal flame temperature is 1350 degrees Celsius

Product Description

This torch has a huge output for its size. The nominal flame temperature is 1350 degrees Celsius, which is ideal for industrial applications. The torch runs on normal cigarette lighter fuel.

Auto Ignition Butane Powered Pro Torch Features

- Large fuel tank for 200 minutes of operating time
- Has self-contained electronic ignition with a waterproof piezo
- Flame adjustment
- Robust construction for professional use

This torch can be used for brazing, soldering, plumbing, industrial maintenance, etc.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

Technical Data

Height: 172mm

Weight: 460g

NOTE: Do not store in environments above 50 degrees Celsius if filled with Butane Gas

Additional Information

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.