

AC TEST SCREWDRIVER 3.5 X 190MM



Part No. ACTEST3

ACTEST3 Test Screwdrivers are conventional neon light indicator lamp style test screwdrivers with GS/TUV and CE approvals, and they have insulated shafts.

EA QTY 1

Driver Tip Width (mm)	3.5mm
Length (mm)	190mm
Weight	27g

WARNING

Do not take risks. Serious injury or death may result if not used correctly. Voltage testers are only to be used by a competent person after reading appropriate instructions.

CAUTION

Voltage test screwdrivers must be proven on a known live source before and after testing.

AC VOLTAGE (NCV) DETECTOR ADJUSTABLE CATIII 600



Part No. C8902A

The C8902A AC voltage detector is suitable for tracing live conductors and breaks in cable. It has an 'on/off' switch and can be adjusted for sensitivity. The ability to adjust sensitivity is used when detecting polarity between Neutral and Active such as in socket outlets.

- Sensitivity adjustment
- Auto-power 'off'
- Visual and audible indication
- Double moulded case
- 2 x 1.5 AAA Batteries

EA QTY 1

Compliance & Safety	IEC61010-1 CATIII 600V
Dimensions	L157 x W24 x T20 mm
Batteries	2 x 1.5 AAA
AC Voltage	12 to 1000V AC 50 to 60 Hz

Packaging C8902A hang cell blister comes with backing card, instructions and batteries.

Weight 42g

WARNING

Do not take risks. Serious injury or death may result if not used correctly. Non contact voltage detectors are only to be used by a competent person after reading appropriate instructions.

CAUTION

Non contact voltage detectors must be proven on a known live source before and after testing. An absence of detection does not mean the circuit under test is dead.

AC VOLTAGE (NCV) DETECTOR ADJUSTABLE CATIII 600



Part No. T7107A

The T7107A AC Voltage Detector is ideal for electrical troubleshooting, detecting a live AC source and locating a burnt out bulb in a series circuit. A bright LED and buzzer alarm informs you that a voltage is present. Features an ergonomic pen shaped design for the ease of carrying and storage. The AC Voltage Detector also includes a Precision Screwdriver for replacing 2 x AAA batteries.

- Voltage Range 50V-1000V AC
- Frequency range 50Hz - 500Hz
- Contact free voltage testing
- Phase detection in sockets
- Rapid detection of cable breaks
- Bright LED
- Variable tone buzzer alarm
- No contact voltage detection

EA QTY 1

Compliance & Safety	IEC61010 CAT IV 1000V, UL,CE
---------------------	------------------------------

WARNING

Do not take risks. Serious injury or death may result if not used correctly. Non contact voltage detectors are only to be used by a competent person after reading appropriate instructions.

CAUTION

Non contact voltage detectors must be proven on a known live source before and after testing. An absence of detection does not mean the circuit under test is dead.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.