

2015S-WE

SOCKET SWITCHED SINGLE 10A 250V WITH SAFETY SHUTTER



Main

| | |
|---------------|----------------|
| Colour | White electric |
| Product brand | Clipsal |

Complementary

| | |
|--------------------------------|-------------------------|
| Colour code | WE |
| Control type | ON/OFF button |
| Number of gangs | 1 gang |
| Pin number | 3 |
| Number of power socket outlets | 1 |
| Actuator | Rocker Switch |
| Mounting position | Horizontal |
| Fixing mode | By screws |
| Local signalling | Without light indicator |
| Material | Plastic |
| Surface finish | Glossy |
| [Ue] rated operational voltage | 250 V AC |
| [In] rated current | 10 A |
| Depth | 12 mm |
| Length | 116 mm |
| Width | 76 mm |
| Fixing center | 84 mm |

Environment

| | |
|-----------|---|
| standards | AS/NZS 3100 AS/NZS 3112 AS/NZS 3133 - approval number S/1 |
|-----------|---|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0928 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.