



### Main

Colour	White electric
Product brand	Clipsal
Device presentation	Basic element with full cover plate and grid

### Complementary

Colour code	WE
Switch function	1-pole
Actuator	Rocker
Number of rocker	3
Device mounting	Flush
Fixing mode	By screws
Material	PC (polycarbonate)
Surface finish	Glossy
Local signalling	Without
[Ue] rated operational voltage	250 V AC
Rated current	10 A
Number of poles	1
Marking	Without marking

### Environment

IP degree of protection	IP66
-------------------------	------

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0946 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.