



Main

Product brand	Clipsal
Colour	Blue

Complementary

Communication network category	6
AWG gauge	AWG 23
Cable stiffness	Class 1 solid
Number of conductors	2 nos.
Cable shielding type	UTP
Cable insulation material	PVC (polyvinyl chloride)
Material	Conductor : bare copper
Diameter	0.57 mm (conductor)
External diameter	6.1 mm
Length	305 m

Environment

ambient air temperature for operation	75 °C
environmental characteristic	Halogen free conforming to EN 50267-2-2 Low smoke emission conforming to EN 61034-2
flame retardance	CM
standards	ANSI/TIA/EIA-568-B ISO/IEC 11801

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.