



### Main

Colour	Transparent
Product brand	Clipsal
Quantity per set	Set of 1
Cover type	Complete housing

### Complementary

Colour code	TR
Marking	Without marking
Local signalling	Without light indicator
Fixing mode	By screws
Material	PVC (polyvinyl chloride)
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC
Depth	71 mm
Diameter	43 mm

### Environment

standards	AS/NZS 3112 AS/NZS 3112 AS 3100 AS 3109 AS/NZS 3122 approval number S/1
-----------	---

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1301 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.