



Main

| | |
|------------------|------------------|
| Colour | Resistant orange |
| Product brand | Clipsal |
| Range of product | Series 56 |
| Voltage colour | Black |

Complementary

| | |
|-------------------------------------|---|
| Colour code | RO |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 500 V 50/60 Hz conforming to EN 60309-2 |
| Duration | 7 h |
| Connections - terminals | Screw terminal |
| Cable entry | Cable gland |
| Plug, socket, control station shape | Straight |
| Material | Plastic |
| Pin arrangement | S |

Environment

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0802 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.