



Main

| | |
|----------------|-----------------|
| Colour | Electric orange |
| Colour code | EO |
| Product brand | Clipsal |
| Voltage colour | Black |

Complementary

| | |
|--------------------------------|-----------------------------|
| Mounting support | Pendant |
| [In] rated current | 20 A |
| [Ue] rated operational voltage | 500 V @ 50/60 Hz EN 60309-2 |
| Duration | 7 h |
| Material | PVC (polyvinyl chloride) |
| Material | PVC (polyvinyl chloride) |
| Mounting mode | External mounting |
| Socket number | 1 |
| Socket-outlet type | R |
| Width | 153 mm |
| Height | 95 mm |

Environment

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0802 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.