

PDL955

In-Line Portable RCD Protected Cordset; 2m, 10A, 30mA Trip, Orange



Main

Range of product	Powerguard Series
Product or component type	Residual current device
Control type	Push-button
Colour tint	Orange

Complementary

Material	PC (polycarbonate)
Surface finish	Gloss
Rated current	10 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Nominal power	2.4 kW
Network number of phases	1 phase
Number of gangs	2 gangs
IP degree of protection	IP33
Ambient air temperature for operation	-10...40 °C
Cable cross section	0.75...1.5 mm ²
Quantity per set	Set of 1
Type of packing	Carton

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 2Q2016 Will be Compliant on 2Q2016
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.