



Main

Range	Wilco Clipsal - Series 4
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Product brand	Clipsal
Device application	Distribution
Poles description	1P + N
Neutral position	Left
Number of modules	2
Number of protected poles	1
[In] rated current	20 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Earth-leakage sensitivity	30 mA
Breaking capacity	6 kA

Complementary

[Ue] rated operational voltage	250 V AC
[Uimp] rated impulse withstand voltage	4 kV
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
Size	81 x 36 x 77.5 mm conforming to DIN 43880

Environment

standards	AS/NZS 61009
IP degree of protection	IP20 conforming to IEC 60529 IP40 for modular enclosure conforming to IEC 60529
ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0851 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.