

PDLS380BW

Back Wiring Mains Switch; 80A/M200, 440V, 50 Hz, 3P, White



Main

| | |
|---------------------------|--------------------|
| Range of product | S Series |
| Product or component type | Switch |
| Material | PC (polycarbonate) |
| Colour tint | White |
| Surface finish | Gloss |

Complementary

| | |
|--------------------------------|--------------------|
| Installation direction | Vertical |
| Width | 52.5 mm |
| Height | 70 mm |
| Depth | 51 mm |
| Rated current | 80 A |
| [Ue] rated operational voltage | 440 V |
| Network frequency | 50 Hz |
| Motor M-rating AS3133 | M200 |
| Number of poles | 3 |
| Mounting mode | Surface mounted |
| IP degree of protection | IP66 |
| Cable cross section | 25 mm ² |
| Quantity per set | Set of 1 |
| Type of packing | Carton |

Environment

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1250 - Schneider Electric declaration of conformity |
| Product end of life instructions | Need no specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.