



product details

64625 HLX

Product description: 64625 HLX
Product code: 4050300006703
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300006703

Applications	
Burning position	s90

Categorizations	
ANSI code	FCR
LIF	A1/215

General Description	
Base (standard designation)	GY6.35

Logistical Data	
Product weight	2.410 g

Technical - Electrical Data	
Construction wattage	100 W
Construction voltage	12 V
Lamp voltage	12 V
Nominal wattage	100 W
Nominal voltage	12 V

Technical - Geometries	
Diameter	11.5 mm
Filament length	4.20 mm
Light center length (LCL)	30 mm
Illuminated field	4.2*2.3 mm ²
Length	44.00 mm
Filament diameter	2.3 mm

Technical - Lifespan	
Lifespan	50 h

Technical - Light Technical Data	
Luminous flux	3600 lm

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300006703	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	6,000 g (0,000 g)	0,040 Cubic dec.
4050300890524	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	242,000 g (0,000 g)	1,864 Cubic dec.

Some lamp models are available as XENOPHOT versions (type HLX).
With xenon instead of krypton as the filler gas, a luminous flux up to 10 % higher is achieved with the same electrical lamp data.

