

ZCKD05

limit switch head ZCKD - without lever spring return
left and or right actuation



ZCK D05



Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKL XCKM XCKS
Associated lever	ZCKY31 ZCKY33 ZCKY34 ZCKY39 ZCKY41 ZCKY43 ZCKY49 ZCKY54 ZCKY55 ZCKY59 ZCKY81 ZCKY91
Associated body	ZCKL1 ZCKL1H7 ZCKL5 ZCKL5H7 ZCKL6 ZCKL6H7 ZCKL7 ZCKL7H7 ZCKL8 ZCKL8H7 ZCKLD31 ZCKLD31H7 ZCKLD35 ZCKLD35H7 ZCKLD37 ZCKLD37H7 ZCKLD39 ZCKLD39H7 ZCKM1 ZCKM1H29 ZCKM1H7 ZCKM5 ZCKM5H29 ZCKM5H7 ZCKM6 ZCKM6H29 ZCKM6H7 ZCKM7 ZCKM7H29 ZCKM7H7 ZCKM8 ZCKM8H29 ZCKM8H7 ZCKM9 ZCKM9H29 ZCKMD31 ZCKMD31H29 ZCKMD31H7 ZCKMD35 ZCKMD35H29 ZCKMD35H7 ZCKMD37 ZCKMD37H29

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

ZCKMD37H7
 ZCKMD39
 ZCKMD39H29
 ZCKMD39H7
 ZCKS1
 ZCKS1H29
 ZCKS2
 ZCKS2H29
 ZCKS404H29
 ZCKS5
 ZCKS5H29
 ZCKS6
 ZCKS6H29
 ZCKS7
 ZCKS7H29
 ZCKS8
 ZCKS8H29
 ZCKS9
 ZCKS9H29
 ZCKSD31
 ZCKSD31H29
 ZCKSD35
 ZCKSD35H29
 ZCKSD37
 ZCKSD37H29
 ZCKSD39
 ZCKSD39H29

Movement of operating head	Rotary
Type of operator	Without operating lever spring return
Type of approach	Lateral approach 1 or 2 programmable direction

Complementary

Switch actuation	From left and/or right CW and/or CCW
Positive opening	With Without
Head material	Plastic

Environment

ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...70 °C
environmental characteristic	Standard environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1012 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations