



Pan-Ty® PLT4H-TL100 Cable Tie, Black, UV Polypropylene, 14.5"L, 50lb, PK250

PLT4H-TL100

Panduit PLT4H-TL100 Locking Cable Ties are designed to satisfy the needs of chemical and weather resistant applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Light-Heavy cross section, 14.5" (368mm) length. Made of Weather Resistant Polypropylene with high resistance to ultraviolet light, are black in color and come in packages of 250.

Specifications

Material Description	Polypropylene (Chemical-Resistant, UV-Resistant, Weather-Resistant)
Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Polypropylene
Resistance Properties	Chemical-Resistant, UV-Resistant, Weather-Resistant
Overall Length (In.)	14.5
Overall Length (mm)	368
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	115
Maximum Operating Temperature (°F)	239
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498353946
Std. Pkg. Qty.	250
Std. Pkg. Volume (cf)	0.2003
Std. Ctn. Qty.	2500
Std. Ctn. Volume (cf)	2.0027