

# XMLA300D2S12

pressure switch XMLA 300 bar - fixed scale 1  
threshold - 1 C/O



## Main

|   |  |
|---|--|
| Range of product  | OsiSense XM  |
| Product or component type                               | Electromechanical pressure sensor  |
| Pressure sensor type                                    | Electromechanical pressure sensor  |
| Device short name                                       | XMLA   |
| Pressure sensor size                                    | 300 bar  |
| Controlled fluid  | Hydraulic oil (0...160 °C)   |
| Fluid connection type                                   | G 1/4 (female) conforming to ISO 228   |
| Electrical connection                                   | Screw-clamps terminals 1 x 0.5...2 x 2.5 mm <sup>2</sup><br>1 connector ISO M20  |
| AWG gauge   | AWG 20...AWG 14  |
| Cable entry   | Cable gland 7...13 mm  |
| Contacts type and composition                           | 1 C/O  |
| Product specific application                            | -  |
| Pressure switch type of operation                       | Detection of 1 single threshold  |
| Electrical circuit type                                 | Control circuit  |
| Scale type  | Fixed differential   |
| Local display   | With   |
| Adjustable range of switching point on rising pressure  | 20...300 bar   |
| Adjustable range of switching point on falling pressure | 3.5...265 bar  |
| Maximum permissible accidental pressure                 | 675 bar  |
| Destruction pressure                                    | 1350 bar   |
| Pressure actuator                                       | Piston   |
| Materials in contact with fluid                         | Brass<br>FPM, FKM<br>PTFE<br>Steel   |
| Enclosure material                                      | Zinc alloy   |
| [In] rated current                                      | 3 A, B300, AC-15 (Ue = 120 V) conforming to EN/IEC 60947-5-1<br>1.5 A, B300, AC-15 (Ue = 240 V) conforming to EN/IEC 60947-5-1<br>0.1 A, R300, DC-13 (Ue = 250 V) conforming to EN/IEC 60947-5-1 |

## Complementary

|  |   |
|--|---|
| Natural differential at low setting      | 16.5 bar (+/- 3 bar)  |
| Natural differential at high setting     | 35 bar (+/- 6 bar)  |
| Maximum permissible pressure - per cycle | 375 bar   |
| Terminal block type                      | 4 terminals   |
| Operating rate                           | 60 cyc/mn   |
| Repeat accuracy                          | < 2 %   |
| [Ui] rated insulation voltage            | 500 V conforming to EN/IEC 60947-1<br>300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage   | 6 kV conforming to EN/IEC 60947-1   |
| Auxiliary contacts operation             | Snap action   |
| Contacts material                        | Silver contacts   |
| Resistance across terminals              | < 25 mOhm conforming to IEC 255-7 category 3  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                          |  |
|--------------------------|--|
|                          | < 25 mOhm conforming to NF C 93-050 method A |
| Short-circuit protection | 10 A cartridge fuse type gG (gl)             |
| Mechanical durability    | 3000000 cycles                               |
| Setting                  | External                                     |
| Height                   | 113 mm                                       |
| Depth                    | 75 mm  |
| Width                    | 35 mm  |
| Product weight           | 0.75 kg                                      |


## Environment

|                                       |  |
|---------------------------------------|--|
| standards                             | CE<br>EN/IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14  |
| product certifications                | BV<br>CCC<br>CSA<br>LROS (Lloyds register of shipping)<br>UL<br>EAC                                  |
| protective treatment                  | TC (standard version)  |
| ambient air temperature for operation | -25...70 °C  |
| ambient air temperature for storage   | -40...70 °C  |
| operating position                    | Any position   |
| vibration resistance                  | 4 gn (f = 30...500 Hz) conforming to IEC 60068-2-6   |
| shock resistance                      | 50 gn conforming to IEC 60068-2-27   |
| electrical shock protection class     | Class I conforming to IEC 1140<br>Class I conforming to IEC 536<br>Class I conforming to NF C 20-030 |
| IP degree of protection               | IP66 conforming to EN/IEC 60529  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Not Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0902 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product end of life instructions | Need no specific recycling operations                                 |

## Dimensions




- (1) 1 fluid entry, tapped G1/4 (BSP female)  
(2) 1 electrical connections entry, tapped M20 x 1.5


Ø : 2 elongated holes Ø 5.2 x 6.7

## Wiring Diagram

### Terminal Model




## Operating Curves



(y) Rising pressure

(x) Falling pressure



(y) Pressure

(x) Time

(1) Adjustable value

(2) Non adjustable value

PH : High point

PB : Below point