56C450LE-RW

56 Series Socket Outlet - 50A - 4 Pin - 3P - 500V - Less Enclosure - White



Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	White RAL 9003

Complementary

•		
Number of poles	4	
Plug, socket category	Low voltage	
Outlet standard	Australian/New Zealand	
Plug, socket, control station shape	Straight	
Number of modules	3	
Number of power socket outlets	1 protective cover	
[ln] rated current	50 A	
[Ue] rated operational voltage	500 V AC 50 Hz	
Poles description	3P + E	
Protection type	Without protection	
Device mounting	Surface	
Material	PC + PET for the cover	
Contacts material	Phosphor bronze for the pins	
Connections - terminals	Screw terminals 1016 mm²	
Electrical connection	Industrial connector	
Depth	45 mm	
Width	101 mm	
Height	198 mm	
Targeted country	Australia	

Environment

standards	AS/NZS 3123
	AS/NZS 3133
ambient air temperature for operation	-2575 °C
IP degree of protection	IP66 conforming to AS 60529

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1501 - Schneider Electric declaration of conformity