



Main

| | |
|---------------------------|---------------------|
| Range of product | Series 56 |
| Range | Clipsal - 56 Series |
| Product brand | Clipsal |
| Product or component type | Socket-outlet |
| Device application | Power supply |
| Colour | Chemical grey |

Complementary

| | |
|-------------------------------------|--|
| Number of poles | 5 |
| Plug, socket category | Low voltage |
| Outlet standard | Australian/New Zealand |
| Plug, socket, control station shape | Straight |
| Number of modules | 3 |
| Number of power socket outlets | 1 protective cover |
| [In] rated current | 50 A |
| [Ue] rated operational voltage | 500 V AC 50 Hz |
| Poles description | 3P + N + E |
| Protection type | Without protection |
| Device mounting | Surface |
| Material | ABS (acrylonitrile butadiene-styrene); cover |
| Contacts material | Pins: phosphor bronze |
| Connections - terminals | Screw terminals cable(s) 10...16 mm ² |
| Electrical connection | Industrial connector |
| Depth | 108 mm |
| Width | 101 mm |
| Height | 204 mm |
| Targeted country | Australia |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | AS/NZS 3123 AS/NZS 3133 |
| Ambient air temperature for operation | -25...75 °C |
| IP degree of protection | IP66 conforming to AS 60529 |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

| | |
|--------------------------|---|
| China RoHS Regulation | Download RoHS China Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
