



Main

Range	Clipsal - 56 Series
Range of product	Series 56
Product brand	Clipsal
Product or component type	Plug
Device application	Power supply

Complementary

[In] rated current	10 A
Poles description	1P + N
[Ue] rated operational voltage	250 V AC 50 Hz conforming to EN 60309-2
Colour	Orange RAL 2004
Material	Plastic
Plug, socket category	Low voltage
Material	Polycarbonate housing
Outlet standard	Industrial
Connections - terminals	Screw terminal 0.75...1 mm ²
Wire stripping length	10 mm 35 mm
Contacts material	Brass pins
Cable entry	Cable gland
Thread type	M20
Plug, socket, control station shape	Straight
Quality labels	RCM
Pin arrangement	D
Service life in hours	4 h
Product weight	0.14 kg
Height	67 mm
Width	67 mm
Depth	112.5 mm
Targeted country	Australia

Environment

standards	AS/NZS 3112
IP degree of protection	IP66 conforming to AS 60529
ambient air temperature for operation	-25...75 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0802 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations