

56SO310ALE-RO

SOCKET OUTLET SURFACE AUTO 10A LESS ENCLOSURE



Main

Colour	Resistant orange
Colour code	RO
Product brand	Clipsal
Voltage colour	Blue

Complementary

Device mounting	Surface
[In] rated current	10 A
Number of poles	2
[Ue] rated operational voltage	230 V @ 50/60 Hz EN 60309-2
Duration	6 h
Connections - terminals	Screw terminal
Material	PVC (polyvinyl chloride)
Material	PVC (polyvinyl chloride)
Mounting mode	External mounting
Socket number	1
Socket-outlet type	A
Depth	39 mm
Width	101 mm
Height	101 mm

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1650 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.