



### Main

|                     |                                     |
|---------------------|-------------------------------------|
| Colour              | Resistant orange                    |
| Product brand       | Clipsal                             |
| Device presentation | Basic element with full cover plate |

### Complementary

|                                |                    |
|--------------------------------|--------------------|
| Colour code                    | RO                 |
| Switch function                | 2-pole             |
| Control type                   | Rotary knob        |
| Device mounting                | Surface            |
| Material                       | PC (polycarbonate) |
| Material                       | PC (polycarbonate) |
| Marking location               | Marking on surface |
| Local signalling               | Without            |
| [Ue] rated operational voltage | 500 V AC           |
| Rated current                  | 20 A               |
| Number of poles                | 2                  |
| Marking                        | ON-OFF             |

### Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP66                         |
| standards               | AS/NZS 3133<br>AS/NZS 3947-3 |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Not Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1650 - Schneider Electric declaration of conformity |
| REACH                            | Reference not containing SVHC above the threshold                     |
| Product end of life instructions | Need no specific recycling operations                                 |