

## 56SW250LE-GY

56 Series - Switch - 2 Pole - 50A - 250V - Less Enclosure - grey



### Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Switch
Device presentation	Basic element with full cover plate
Device application	Control
Colour	Grey for cover
Handle colour	Grey
Suitability for isolation	Yes

### Complementary

Switch function	2-pole
Poles description	2P
Control type	Rotary knob
Number of poles	2
Device mounting	Surface
Connections - terminals	Screw terminal 10...25 mm <sup>2</sup> cable stiffness solid
Material	PC (polycarbonate)
Tightening torque	0.8 N.m
Local signalling	Without
[Ue] rated operational voltage	250 V AC 50 Hz
Rated current	50 A
Breaking capacity	50 kA
Motor M-rating AS3133	M250 at 250 V
Rotary handle padlocking	2 padlocks of 8 mm diameter
Marking	ON-OFF
Marking location	Marking on surface
Height	107 mm
Width	101 mm
Depth	72 mm
Product weight	0.001 kg
Targeted country	Australia

### Environment

ambient air temperature for operation	-25...75 °C
IP degree of protection	IP66 conforming to AS 60529
standards	AS/NZS 3133

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1501 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.