

PDL951OR

Powerguard Portable RCD; 10A, 230 - 240VAC,
30mA Trip, Orange



Main

Range of product	Powerguard Series
Product or component type	Residual current device
Control type	Push-button
Material	PC (polycarbonate)
Colour tint	Orange

Complementary

Surface finish	Gloss
Rated current	10 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Nominal power	2.4 kW
Network number of phases	1 phase
Number of poles	2
IP degree of protection	IP3x
Ambient air temperature for operation	-10...40 °C
Cable cross section	0.75...1.5 mm ²
Product specific application	RCD adaptor for personal protection requirements
Quantity per set	Set of 1
Type of packing	Blister

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 2Q2016 Will be Compliant on 2Q2016
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.