

ST Fibre Pigtails

The Simplex ST Fibre Pigtails are 3.0mm cordage with push-pull ST connectors terminated on each end. These pigtails are available in Simplex Multi-Mode configurations.

PHYSICAL SPECIFICATIONS

Coated Fibre Diameter	250µm
Cable Outside Diameter	Simplex: 3.0mm
Min. Bend Radius	3.8cm

OPTICAL SPECIFICATIONS

Multi-Mode	
Min. Bandwidth @850nm @1300nm	200MHz-km 500MHz-km
Single-Mode	
Average Loss	0.3dB/mated connector
Return Loss	-50dB max.



TFT1T3S19S05

PRODUCT FEATURES

- Meets ANSI/TIA/EIA 568-B.3 and ISO/IEC 11801 Standards.
- Patch cords are available in Simplex, Single-Mode and Multi-Mode configurations with different length options.
- Cords are easy-to-install and environmentally stable.

CUSTOMER BENEFITS

- Supports LAN, WAN and active device termination.
- Provides a reliable and durable connection solution.
- All cords are factory terminated and tested.

CATALOGUE NUMBER	DESCRIPTION
OS1, Single-Mode	
TFT1T3S19S05	ST, Simplex, OS1, Single-Mode, 9/125µm, Fibre Pigtail, 0.5m
TFT1T3S19S10	ST, Simplex, OS1, Single-Mode, 9/125µm, Fibre Pigtail, 1.0m
TFT1T3S19S15	ST, Simplex, OS1, Single-Mode, 9/125µm, Fibre Pigtail, 1.5m
TFT1T3S19S20	ST, Simplex, OS1, Single-Mode, 9/125µm, Fibre Pigtail, 2.0m
OM1, Multi-Mode	
TFT1T3M16M05	ST, Simplex, OM1, Multi-Mode, 62.5/125µm, Fibre Pigtail, 0.5m
TFT1T3M16M10	ST, Simplex, OM1, Multi-Mode, 62.5/125µm, Fibre Pigtail, 1.0m
TFT1T3M16M15	ST, Simplex, OM1, Multi-Mode, 62.5/125µm, Fibre Pigtail, 1.5m
TFT1T3M16M20	ST, Simplex, OM1, Multi-Mode, 62.5/125µm, Fibre Pigtail, 2.0m
OM3, Multi-Mode	
TFT1T3M35M05	ST, Simplex, OM3, Multi-Mode, 50/125µm, Fibre Pigtail, 0.5m
TFT1T3M35M10	ST, Simplex, OM3, Multi-Mode, 50/125µm, Fibre Pigtail, 1.0m
TFT1T3M35M15	ST, Simplex, OM3, Multi-Mode, 50/125µm, Fibre Pigtail, 1.5m
TFT1T3M35M20	ST, Simplex, OM3, Multi-Mode, 50/125µm, Fibre Pigtail, 2.0m