

## WMC310

Clipsal Wilco Rowco - Switched Socket Outlet - 10A  
- 3 Pin - 1 Pole - 250V



### Main

Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Yellow

### Complementary

Number of poles	2
Plug, socket category	Low voltage
Outlet standard	Australian/New Zealand
Plug, socket, control station shape	Straight
Number of modules	2
Number of power socket outlets	1 protective cover
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC 50 Hz
Poles description	1P + N + E
Protection type	Without protection
Device mounting	Surface
Material	Aluminium for the cover
Contacts material	Phosphor bronze for the pins
Connections - terminals	Screw terminals 1.5...16 mm <sup>2</sup>
Electrical connection	Industrial connector
Depth	116 mm
Width	99 mm
Height	201 mm
Targeted country	Australia

### Environment

standards	AS/NZS 3112 AS/NZS 4417.1
ambient air temperature for operation	-25...75 °C
IP degree of protection	IP66 conforming to AS 60529

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.