



Main

Range	C-Bus
Product brand	Clipsal
Product or component type	Dimmer
Device application	Control
Device presentation	Basic element
Dimmer type	Universal

Complementary

Power consumption in VA	20 VA
[Ue] rated operational voltage	220...240 V AC
Network frequency	47...53 Hz
Nominal output power	600 W
Number of modules	12
Local signalling	LED
Number of channels	4
Mounting support	DIN rail
Size	215 x 85 x 65 mm base

Environment

IP degree of protection	IP20
standards	EN 60669-2-1 AS/NZS 3100 AS/NZS 4051 AS/NZS 61558-1

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1121 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.