

LC1F4004

TeSys F contactor - 4P(4 NO) - AC-1 - <= 440 V 500 A - without coil



Main

| | |
|--------------------------------|--------------------------------------|
| Range | TeSys |
| Product name | TeSys F |
| Product or component type | Contacteur |
| Device short name | LC1F |
| Contacteur application | Resistive load |
| Utilisation category | AC-1 |
| Poles description | 4P |
| Pole contact composition | 4 NO |
| [Ue] rated operational voltage | <= 1000 V AC 50/60 Hz <= 460 V DC |
| [Ie] rated operational current | 500 A (<= 40 °C) at <= 440 V AC AC-1 |

Complementary

| | |
|---|--|
| [Uimp] rated impulse withstand voltage | 8 kV |
| Overtoltage category | III |
| [Ith] conventional free air thermal current | 500 A at <= 40 °C |
| Irms rated making capacity | 4000 A AC conforming to IEC 60947-4-1 |
| Rated breaking capacity | 3200 A conforming to IEC 60947-4-1 |
| [Icw] rated short-time withstand current | 3600 A <= 40 °C 10 s 2400 A <= 40 °C 30 s 1700 A <= 40 °C 1 min 1200 A <= 40 °C 3 min 1000 A <= 40 °C 10 min |
| Associated fuse rating | 400 A aM at <= 440 V 500 A gG at <= 440 V |
| Average impedance | 0.26 mOhm at 50 Hz - Ith 500 A |
| [Ui] rated insulation voltage | 1000 V conforming to IEC 60947-4-1 1500 V conforming to VDE 0110 group C |
| Power dissipation per pole | 65 W AC-1 |
| Mounting support | Plate |
| Standards | EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JIS C8201-4-1 |
| Product certifications | ABS BV CSA DNV LROS (Lloyds register of shipping) RINA RMRoS UL CB |
| Connections - terminals | Power circuit : lugs-ring terminals 2 cable(s) 150 mm ² Power circuit : bar 2 x (30 x 5 mm) |
| Tightening torque | Power circuit : 35 N.m |

Environment

| | |
|-------------------------|---|
| IP degree of protection | IP20 front face with shrouds (ordered separately) conforming to IEC 60529 IP20 front face with shrouds (ordered separately) conforming to VDE 0106 |
|-------------------------|---|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| protective treatment | TH |
| ambient air temperature for operation | -5...55 °C |
| ambient air temperature for storage | -60...80 °C |
| permissible ambient air temperature around the device | -40...70 °C |
| operating altitude | 3000 m without derating |
| mechanical robustness | Shocks resistance contactor closed 15 Gn for 11 ms Shocks resistance contactor open 6 Gn for 11 ms Vibrations resistance contactor closed 5 Gn, 5...300 Hz Vibrations resistance contactor open 1.5 Gn, 5...300 Hz |
| height | 206 mm |
| width | 261 mm |
| depth | 219 mm |
| product weight | 8 kg |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0852 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |