



Main

Range of product	NG125
Range	Acti 9
Product name	Acti 9 NG125
Product or component type	Miniature circuit-breaker
Device short name	NG125H
Device application	Distribution
Poles description	1P
Number of protected poles	1
[In] rated current	20 A at 40 °C
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	36 kA Icu conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz 70 kA Icu conforming to EN/IEC 60947-2 - 110...130 V AC 50/60 Hz 36 kA Icu conforming to EN/IEC 60947-2 - 12 V DC 36 kA Icu conforming to EN/IEC 60947-2 - 125 V DC 25 kA Icu conforming to EN/IEC 60947-2 - <= 144 V DC 9 kA Icu conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz
Utilisation category	Category A conforming to IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	12 V DC 125 V DC 220...240 V AC 50/60 Hz 380...415 V AC 50/60 Hz 110...130 V AC 50/60 Hz <= 144 V DC
Magnetic tripping limit	8 x In
[Ics] rated service breaking capacity	52.5 kA at 75 % of breaking cap. conforming to EN/IEC 60947-2 - 110...130 V AC 50/60 Hz 27 kA at 75 % of breaking cap. conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz 6.75 kA at 75 % of breaking cap. conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz 36 kA at 100 % of breaking cap. conforming to EN/IEC 60947-2 - 60 V DC 36 kA at 100 % of breaking cap. conforming to EN/IEC 60947-2 - 125 V DC
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle Manual tripping test
Local signalling	ON/OFF indication Trip indicator
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Comb busbar distribution block compatibility	YES
9 mm pitches	3

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Height	103 mm
Width	27 mm
Depth	81 mm
Product weight	0.24 kg
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Locking options description	Integrated padlocking
Connections - terminals	
Wire stripping length	20 mm
Tightening torque	3.5 N.m
Earth-leakage protection	Without

Environment

standards	EN/IEC 60947-2
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK05 conforming to EN/IEC 62262
pollution degree	3 conforming to IEC 60947-2
overvoltage category	IV
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % 55 °C
ambient air temperature for operation	-30...70 °C
ambient air temperature for storage	-40...70 °C