

MODEL 1009



- Display : 4000 counts.
- Auto range and manual range selector provided. (with range hold feature)
- Resistance range provides audible continuity test.
- Automatically turns power off in about 30 minutes to conserve battery life.
- Direct current measurement up to 10A AC and DC.
- With Holster.

	1009
DC V	400mV/4/40/400/600V(Input impedance 10M Ω) $\pm 0.6\%rdg \pm 4dgt(400mV/4/40/400V) \pm 1.0\%rdg \pm 4dgt(600V)$
AC V	400mV/4/40/400/600V(Input impedance 10M Ω) $\pm 1.6\%rdg \pm 4dgt(20 \sim 400mV) \pm 1.3\%rdg \pm 4dgt(4/40V)$ $\pm 1.6\%rdg \pm 4dgt(400/600V)$
DC A	400/4000 μ A/40/400mA/4/10A $\pm 2.0\%rdg \pm 4dgt(400/4000\mu A) \pm 1.0\%rdg \pm 4dgt(40/400mA)$ $\pm 1.6\%rdg \pm 4dgt(4/10A)$
AC A	400/4000 μ A/40/400mA/4/10A $\pm 2.6\%rdg \pm 4dgt(400/4000\mu A)$ $\pm 2.0\%rdg \pm 4dgt(40/400mA/4/10A)$
Ω	400 Ω /4/40/400k Ω /4/40M Ω $\pm 1.0\%rdg \pm 4dgt(400\Omega/4/40/400k\Omega/4M\Omega)$ $\pm 2.0\%rdg \pm 4dgt(40M\Omega)$
Continuity buzzer	400 Ω (Buzzer sounds below 70 Ω)
Diode test	1.5V Release Voltage : Approx. 0.4mA test current
Capacitance test	40/400nF/4/40/100 μ F
Frequency	5.12/51.2/512Hz/5.12/51.2/512kHz/5.12/10MHz
DUTY	0.1~99.9%(Pulse width/Pulse period) $\pm 2.5\% \pm 5dgt$
Applicable standards	IEC 61010-1 CAT. III 300V IEC 61010-031 IEC 61326-1
Power source	R6P(1.5V) \times 2 (Auto power off : approx. 30 minutes)
Dimensions	155(L) \times 75(W) \times 33(D)mm
Weight	260g approx.
Accessories	7066A(Test leads) 8919(Ceramic fuse[10A/600V]) \times 1 8923(Ceramic fuse [0.5A/600V]) \times 1 R6P \times 2 Instruction manual