

KT 200

AC CLAMP METER



- Small and handy clamp meter
- IEC61010-1 Safety Standard CAT. III 300V, CAT. II 600V
- 400A AC Clamp meter
- DMM function ACV, DCV, Ω Continuity Buzzer.



	KT 200
AC A	40.00/400.0A ±2.0%rdg±6dgt(50/60Hz)
AC V	400.0/600V(Auto-ranging) ±2.0%rdg±5dgt(50/60Hz)
DC V	400.0/600V(Auto-ranging) ±1.5%rdg±5dgt
Ω	400.0/4000Ω(Auto-ranging) ±2.0%rdg±5dgt
Continuity buzzer	buzzer sounds below 50±35Ω
Conductor size	φ30mm max.
Applicable standards	IEC 61010-1 CAT.III 300V(ACA), CAT.II 600V Pollution degree 2 IEC 61010-031, IEC61010-2-032, IEC61326-1
Power source	R03(1.5V)(AAA) x 2 *Continuous measuring time:approx.200 hours(Auto power save: approx.10 minutes)
Dimensions	184(L) x 68.6(W) x 38.5(D)mm
Weight	Approx. 190g(including batteries)
Accessories	7066A(Test leads), R03(AAA) x 2, Instruction manual
Optional	9105(Carrying case)