Queensland Raiser Brackets & Accessories

Accessories for QLD metering enclosures













- Suitable for use on all QLD domestic and commercial overhead mains installations.
- Used as a point of attachment for above ground service mains to the premises.
- Designed and tested to QLD supply authority rules & regulations.
- 1.0kN strength rating
- Tested to meet ECMM requirements.
- Manufactured from hot dipped galvanised steel to AS/NZS4680



ORDERING GUIDE - RAISER BRACKETS

Part Number	Product	Size (mm)
2F		600
3F	Fascia mounting	900
4F		1200
3NQF	Fascia mounting (North Qld)	900
RBSK	Raiser bracket stay kit	_
QSPK360	Qld side pull kit 360°	_







ORDERING GUIDE - MAINS CONNECTION ENCLOSURES

Dimensions (mm)

Part Number	Product	Height	Width	Depth	Cover Depth	Usable Depth	Weight (kg	
PC362720	Dalamana DO IDOS analasana	360	270	205	75	170	3.2	
PC543617	Polynova PC IP66 enclosure	540	360	170	45	135	5.7	
PM3627	Delumente DM IDGE en el conse	360	270	165	40	140	2.6	
PM5436	Polynova PM IP65 enclosure	540	360	165	40	140	5.0	

ORDERING GUIDE - ACCESSORIES

Spacer required for compliance.

Part Number	Product	PC362720	PC543617	PM3627	PM5436
Tait Number	Troduct				
PCFD5436	Depth spacer 62.5mm		•		
PM3627/S	Donath on one (non-negative)			•	
PM5436/S	Depth spacer (non-metallic)				•





Polynova PC enclosure Polynova PM depth spacer