Horizon W Series

Residential metering enclosures for WA applications

















- Designed for both single and multi-phase installations.
- Provides safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Easy-to-use gravity catch.
- Ratchet sliding cable entry.
- RotaDIN rotating / removable DIN section.
- Cord retainer for easy retention of extension cords.
- Identification with covered labelling section.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- · External frame mounting brackets.
- Meter lock-off device.
- Manufactured from 1.0 galvanised steel to Z275.
- Powdercoated Light Grey RAL7035.



ORDERING GUIDE

| | | Dimensions (mm) | | | |
|-------------|-----------|-----------------|-------|-------|--|
| Part Number | DIN space | Height | Width | Depth | |
| W10 | 24-pole | 520 | 485 | 278 | |

ACCESSORIES

| Part Number | Product | | Dimensions (mm) | | 0 |
|-------------------------|--------------------|---|-----------------|-------|-----|
| | | Description | Height | Width | W10 |
| HZN/JK2 [†] | Bolt kit | For combining with a HZN/COM [^] enclosure | _ | _ | • |
| WADIN24/24 [†] | | 3 rows, 24 pole | _ | - | • |
| WADIN16/24 [†] | DIN rail kits | 16 pole escutcheon, 24 pole base | - | - | • |
| WADIN08 [†] | _ | 1 row, 8 poles | - | _ | • |
| BRS-Q3027 [†] | Moulded panel | 450mm high x 225mm wide | 450 | 225 | • |
| BMP0402/06 | | 0 1111 | 450 | 225 | • |
| BMP0404/06 | — Insulated panels | 6mm thick | 450 | 450 | • |



[†]While stock lasts.

[^] For more information on the HZN/COM enclosure range please refer to page 12.