



MCB 2P 10kA C-2A 2M

Similar image  
(Picture shows NT216C)

|                                                                         |                            |
|-------------------------------------------------------------------------|----------------------------|
| Technical Properties                                                    |                            |
| Number of modules                                                       | 2                          |
| Number of poles                                                         | 2 P                        |
| Rated short circuit breaking capacity Icn AC according 10 kA IEC60898-1 |                            |
| Curve                                                                   | C                          |
| Rated operational voltage Ue                                            | 415 V                      |
| Rated current                                                           | 2 A                        |
| Frequency                                                               | 50/60 Hz                   |
| Rated insulation voltage                                                | 500 V                      |
| Operating temperature                                                   | -25 to 60 °C               |
| Electric endurance in number of cycles                                  | 4000                       |
| Number of mechanical operations                                         | 20000                      |
| Top and bottom screw terminals connection capacity with rigid cable     | 1/25 mm²                   |
| Top and bottom screw terminals connection capacity with flexible cable  | 1/16 mm²                   |
| Tightening torque                                                       | 2,8Nm                      |
| Height of installed product                                             | 83 mm                      |
| Width of installed product                                              | 35 mm                      |
| Depth of installed product                                              | 70 mm                      |
| Standard text                                                           | EN 60898-1 ; AS/NZ 60898-1 |