

Queensland Series

Residential metering enclosures for QLD applications



- Designed for both single and multi-phase installations.
- Durable enclosure suitable for domestic and light metering installations.
- Slide and lift off escutcheon.
- Concealed lift off hinges.
- Underground service location label.
- Double return flat face gutter.
- Manufactured from 1.0 galvanised steel to Z275.
- Powdercoated Light Grey RAL7035.



ORDERING GUIDE

Part Number	DIN space	Inclusions			Dimensions (mm)			Panel (mm)		
		RCCB Link [#]	Busbar	ID labels	Height	Width	Depth	Height	Width	Depth Behind
BR1M/SL* [†]					515	365	275	480	340	75
BR1M/ECB	22-pole	•	•	•	685	485	275	480	461	75
BR1M/ECB/SL	15-pole	•	•	•	685	365	275	380	340	75
BR3M*					600	620	275	566	600	75
BR3M/ECB	24-pole	•	•	•	770	620	275	566	600	75
NQ/DIN [^]	18-pole	•	•	•	600	600	270	575	560	75
CSQ042201 [†]		•	•		520	485	278	480	461	75

* For remote load centre installations

[#] RCCB Links provide RCD expansion to 3 circuits

[^] Not suitable for ERGON metering

[†] While stocks last

ACCESSORIES

Part Number	Description						CSQ42201
		BR1M/SL	BR1M/ECB	BR1M/ECB/SL	BR3M	BR3M/ECB	
QNPLK	Padlocking kit to suit all QLD series enclosures	•	•	•	•	•	
ECBCK [†]	Temporary power conversion kit		•		•	•	

[†] While stocks last



QNPLK[†]



ECBCK