

2 pole Changeoverswitch 63A I-0-II

SF263

Number of modules Number of poles Type of contacts Rated operational voltage Ue Rated current 63 A Rated operational current in AC21 Short circuit current withstand with MCB 63A Curve C 4,5 kA Total power loss under IN Frequency Sol/60 Hz Rated insulation voltage Fated impulse withstand voltage Operating temperature Electrical durability at nominal load in AC21in 2 P Changeover with zero position AG A Short circuit current withstand with MCB 63A Curve C 4,5 kA - 4,5 kA Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 500 V Solve Total power loss of the power	Technical Properties	
Type of contacts changeover with zero position Rated operational voltage Ue 230 V Rated current 63 A Rated operational current in AC21 63 A Short circuit current withstand with MCB 63A Curve C 4,5 kA - 4,5kA Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Number of modules	4
Rated operational voltage Ue Rated current Rated operational current in AC21 Short circuit current withstand with MCB 63A Curve C 4,5 kA - 4,5kA Total power loss under IN Frequency Sol/60 Hz Rated insulation voltage Rated impulse withstand voltage Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in	Number of poles	2 P
Rated current 63 A Rated operational current in AC21 63 A Short circuit current withstand with MCB 63A Curve C 4,5 kA - 4,5kA Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Type of contacts	changeover with zero position
Rated operational current in AC21 63 A Short circuit current withstand with MCB 63A Curve C 4,5 kA - 4,5kA Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Rated operational voltage Ue	230 V
Short circuit current withstand with MCB 63A Curve C 4,5 kA - 4,5kA Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Rated current	63 A
- 4,5kA Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Rated operational current in AC21	63 A
Total power loss under IN 3,6 W Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Short circuit current withstand with MCB 63A Curve C	4,5 kA
Frequency 50/60 Hz Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	- 4,5kA	
Rated insulation voltage 500 V Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Total power loss under IN	3,6 W
Rated impulse withstand voltage 4000 V Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Frequency	50/60 Hz
Operating temperature -20 to 50 °C Electrical durability at nominal load in AC21in 5000	Rated insulation voltage	500 V
Electrical durability at nominal load in AC21in 5000	Rated impulse withstand voltage	4000 V
·		-20 to 50 °C
an anathra a carala a	Electrical durability at nominal load in AC21in	5000
operating cycles	operating cycles	
Number of mechanical operations 100000	Number of mechanical operations	100000
Connection cross-sect. rigid cable 25mm ²	Connection cross-sect. rigid cable	25mm²
Connection cross-sect. flexible cable 16mm ²	Connection cross-sect. flexible cable	16mm²
Height of installed product 90 mm	Height of installed product	90 mm
Width of installed product 71,5 mm	Width of installed product	71,5 mm
Depth of installed product 72 mm	Depth of installed product	72 mm
Tightening torque 2,9Nm	Tightening torque	2,9Nm
Protection index IP IP20	Protection index IP	IP20