



VT24S

## 24M 2Row DIN Surface Metal BOX, No Door

### Architecture

Fixing mode	surface-mounting
-------------	------------------

### Compatibility

Cabinet profile measurement standard	metric
Suitable for lightning protection	yes

### Main electrical features

Nominal voltage	230 / 415 V AC
-----------------	----------------

### Cover, door

Material thickness cover	1 mm
Interlockable	no
Cover type	Closed (plain)
Door lock can be sealed	no
Door leave	without
Symmetric doors (same width)	no
Cover type	Cover
Door included	no
Transparent cover or door	no

### Materials

Colour	light grey
RAL colour	RAL 9002 - Grey white
Material	Steel
Material quality	Steel
Surface appearance	satın finish
Type of surface treatment	Painted

### Dimensions

Insertion depth	70 mm
Depth of installed product	71 mm
Internal depth	68 mm
Height of installed product	419 mm
Width of installed product	369 mm
Width in division units	12
Thickness of sidewall material	1 mm

#### Installation, mounting

Suitable for outdoor use	no
Suitable for ground mounting	no
Suitable for wall mounting	yes

#### Accessories included

Mounting plate included	no
-------------------------	----

#### Equipment

Number of rows	2
Quantity of rails	2
On/Off switch	no
Extension possible	no

#### Standards

Approvals	AS/NZS 61439-3
-----------	----------------

#### Safety

IK protection code against mechanical impacts	IK05
Protection class	isol.class I
Glow wire test	according to AS/NZS 61439-1
Halogen free	no
Fire resistance	-