


FLEXIBLE DUCT (NON-INSULATED)



- Suitable for general exhaust and supply air applications such as bathrooms, ensuites and toilets.
- Fibre woven metallic duct provides durability and tear resistance.
- High tensile wire sprung to retain duct shape and flexibility.
- Complies with Australian/New Zealand Standards: Construction contains high grade flame retardant with a 3 zero fire rating - AS/NZS 4254.

PART NO.	DUCT DIAMETER, MM	DUCT LENGTH, M	BULK PACK CONTENTS	TRADE PACK CONTENTS
DUCT100-3MPK	100	3	-	-
DUCT125-3MPK	125	3	-	-
DUCT100-6M	100	6	20 lengths	-
DUCT100-6M-TP-100	100	6	-	100 lengths
DUCT125-6M	125	6	20 lengths	-
DUCT150-6M	150	6	20 lengths	-
DUCT150-6M-TP-70	150	6	-	70 lengths
DUCT200-6M	200	6	20 lengths	-
DUCT250-6MP	250	6	-	-
DUCT300-6MP	300	6	-	-

FLEXIBLE DUCT (INSULATED)



- Thermally insulated outer sleeve to minimise heat gain or heat loss.
- Fibre woven metallic inner duct provides durability and tear resistance.
- High tensile wire sprung to retain duct shape and flexibility.
- Complies with Australian/New Zealand Standards: Construction contains high grade flame retardant with a 3 zero fire rating - AS/NZS 4254.

PART NO.	DUCT DIAMETER, MM	DUCT LENGTH, M
DUCT150INS-6M	150	6
DUCT200INS-6M	200	6
DUCT250INS-6M	250	6

SEMI-RIGID ALUMINIUM DUCTING




- Well suited to clothes dryers, range hoods, bathrooms and other general ventilation applications as it holds its shape when formed around obstacles.
- Temperature rating -70°C to +220°C.
- Complies with Australian/New Zealand Standards:
 - Fire and smoke control - AS/NZS 1668.1
 - 3 zero fire rating - AS/NZS 1530.3
 - Flexible ductwork - AS 4254

PART NO.	DUCT DIAMETER, MM	DUCT LENGTH, M	COMPRESSED, MM
DUCT100-3-SRIG	100	3	750
DUCT125-3-SRIG	125	3	750
DUCT150-3-SRIG	150	3	750
DUCT200-3-SRIG	200	3	750




FlexRight installation in a duct system



FLEXRIGHT DUCT ELBOW

The FlexRight Duct Elbow is designed to improve the efficiency of a heating and air conditioning system. It does this by removing kinks in ductwork and creating a 90° bend with a large and smoother radius which improves air flow.

- Helps minimise load on ducted heating & cooling units
- Suitable for both new and existing duct installations
- Reduces noise from your system



PART NO.	SUIT DUCT DIAMETER, MM
FR-2	100 to 400



Y Piece (YP)

Branch Take Off (BTO)

Y-PIECES AND BRANCH TAKE OFFS

Designed to divide air flow in ducted systems. Made from injected-moulded ABS flame retardant material.

PART NO.	DUCT DIAMETER, MM (FAN SIDE)	NO. OF DUCT BRANCHES	BRANCH DIAMETERS, MM
YP-100-100-100*	100	2	100
YP-125-125-125*	125	2	125
YP-150-150-150	150	2	150
BTO-150-150-150	150	2	150
YP-200-150-150	200	2	150
BTO-200-200-150	200	2	200 & 150
YP-250-200-200	250	2	200
YP-250-250-250	250	2	250
YP-300-300-300	300	2	300
YP-300-200-200	300	2	200

* Made from metal




Double Branch Take Off (DBTO)

DOUBLE BRANCH TAKE OFFS

Designed to divide air flow in ducted systems. Made from injected-moulded ABS flame retardant material.

PART NO.	DUCT DIAMETER, MM (FAN SIDE)	NO. OF DUCT BRANCHES	BRANCH DIAMETERS, MM
DBTO-200-3X150	200	3	150
DBTO-250-3X200	250	3	200
DBTO-300-3X200	300	3	200



DUCT JOINER

Sheet steel piece allowing the connection of two ducts of the same diameter.

PART NO.	JOINER DIAMETER, MM
JOINER100	100
JOINER125	125
JOINER150	150
JOINER200	200
JOINER250	250
JOINER300	300



DUCT REDUCER

Allows duct of two different diameters to be joined together. Made from injected-moulded ABS flame retardant material.

PART NO.	DUCT DIAMETER, MM (FAN SIDE)	BRANCH DIAMETERS, MM
RED125-100	125	100
RED150-100	150	100
RED150-175	150	175
RED200-150	200	150
RED250-200	250	200
RED300-200	300	200
RED300-250	300	250
RED315-300	315	300



CIRCULAR REDUCER/EXPANDERS

Designed to join duct of two different diameters together.

CIRCULAR REDUCER / EXPANDERS	DESCRIPTION	CODE
	Circular reducer / expander Ø125mm to Ø100mm	FPD-RED125/100
	Circular reducer / expander Ø150mm to Ø100mm	FPD-RED150/100
	Circular reducer / expander Ø150mm to Ø125mm	FPD-RED150/125
	Circular reducer / expander Ø200mm to Ø150mm	FPD-RED200/150