


GEMGK350 SURFACE MOUNT ELECTRIC STRIKE

The GK-350 series surface mount electric strikes are designed for use with night latch locks (without deadbolt) having up to 12mm throw latchbolt.

The units are design for use with most hollow metal frames, aluminum frames and wood frames. Stainless steel plate ensures strength and long life.






SPECIFICATIONS

Power Input	12 V DC (24V DC available by special order)
Voltage Tolerance	±15%
Current Draw	0.25 A@12 VDC; 0.15 A@24 VDC (at temperature 20°C)
Operating Temperature	-10~45°C
Humidity	0~95% non-condensing
Lock's surface Temperature (when the power is on)	≤ current temperature +20°C
2000 LBS jaw strength pull testing	Tested to 1,000,000 cycles
Weight (Approx.)	330 g

VERSION CHANGEABLE


Field-reversible (by changing position of screws) on site for Fail-safe (Power to Lock) or Fail-secure (Power to Open) in 10 seconds.




LONG LIFE SOLENOIDS

Strikes are powered by a solenoid, not a buzzer coil. Special designed solenoid for strength and long life operating lifetime with guaranteed 1,000,000 operations.

HOLLOW FRAMES SURFACE MOUNT INSTALLATION



WOOD FRAMES SURFACE MOUNT INSTALLATION



FIRE • SECURITY • INTERCOMS

