



**PART No. H3C-R**

## Quick Overview

Multi Function Analogue Timer

## Features

### Timers

#### Multi Function Analogue Timer

- Wide operating voltage range in a single unit, AC/DC 24V-240V
- 8 field-selectable output modes for various applications
- 14 field-selectable time range, from 0.2 second to 300 hour
- Includes 2C output contacts, instantaneous output contact, flicker and interval modes
- Short body design, 68mm
- Adaptor Y-57 for different flush mount
- UL, C-UL, recognised and CE certified

#### Specifications:

- Operating voltage: AC/DC, 24-240V
- Allowable operating voltage range: 85-110% of rated operating voltage
- Rated frequency: 50/60 Hz
- Contact rating: 250 VAC 5A (resistive load)
- Reset time: Max 0.1S
- Power consumption: Approx. 3VA
- Life: Mechanical: 5,000,000 times/Electrical: 100,000 times
- Ambient temperature: -10~ + 50 °C
- Ambient humidity: Max 85% RH
- Output contact: 2C or 1A2C

- Time range: 1.2s, 3s, 12s, 30s, 1.2m, 3m, 12m, 30m, 1.2h, 3h, 12h, 30h, 120h, 300h
- External reset: No
- External start: No
- External gate: No
- Mounting base PF083A-E sold separately
- Weight: Approx. 100g

## Details

Part No.	H3C-R
Brand	Anly
Unit Of Measure	Each
Carton Quantity	1
Compendium Page #	607

Proudly Distributed By



1300 555 586  
www.repelec.com.au

Sign up or log in to repelec.com.au  
@RepelecAU