

Quick Overview

Raychem CRSM Cable Repair Sleeve



Features

Raychem CRSM Cable Repair Sleeve

- Heat shrinkable wraparound system for cable sheath repair
- Cable sheath repair up to 36kV
- Primary insulation repair to 1kV
- Corrosion protection
- Street lighting joints
- Environmental seals

Details

Part No.	RAYCRSM143/36
Brand	Raychem
Unit Of Measure	Each
Compendium Page #	362

Additional Information

Part No.	Application Range (Diameter mm)	Diameter		Width (Flat)		Wall Thickness	
		As Supplied Minimum (mm)	After Free Recovery Maximum (mm)	As Supplied Minimum (mm)	After Free Recovery Minimum (mm)	As Supplied Minimum (mm)	After Free Recovery *Minimum (mm)
RAYCRSM34/10	11–21	35	9	110	35	0.3	2.4
RAYCRSM53/13	17–32	54	15	170	49	0.3	2/0
RAYCRSM84/20	24–50	86	21	270	69	0.3	2.0
RAYCRSM107/29	31–65	108	27	340	90	0.3	2.0
RAYCRSM143/36	33–86	144	28	455	119	0.3	1.8
RAYCRSM198/55	56–120	203	50	640	172	0.3	2.1

Note: • Standard lengths of 1000 and 1500 mm.
• Maximum longitudinal change after free recovery: -0 – +10%
* At minimum supplied width.