



Quick Overview

Utilux Copper Crimp Lugs

Features

Utilux Copper Crimp Lugs

- Suitable for copper conductor
- Range 0.5-1200 mm²
- Seamless copper tube
- Electro tinned
- Cable area clearly identified on the lug
- Tested to AS/NZS 4325.1:1995

Details

Part No.	UTIH1365/50
Brand	Utilux
Pack Quantity	50
Unit Of Measure	Box
Compendium Page #	307

Additional Information

Part No.	Description	Conductor mm² Stranding	Stud Size	Dimensions A B C D F G						Number of Crimps						Die A/F (mm)
										Indent				Hex		
										76	00	18	20	22	38A	
UTIH1399/100	CG0.5M4	0.5 1/0.80	M4	18	6.4	1.4	9	6	2.1	1	1	1	-	-	-	-
UTIH1400/100	CG0.5M4		M4	19	6.4	1.4	11	6	2.1	1	1	1	-	-	-	-
UTIH1401S/100	CG0.5SM5		M5	19	8.7	1.0	11	6	2.1	1	1	1	-	-	-	-
UTIH1402/100	CG0.5M6		M6	26	10	0.9	15	9	2.1	2	2	1	-	-	-	-
UTIH1402A/100	CG0.5M8		M8	26	11	0.8	15	9	2.1	2	2	1	-	-	-	-
UTIH1436A/100	CG2.5M4	2.5 7/0.67	M4	21	9.1	1.1	12	8	2.5	2	1	1	-	-	-	-
UTIH1436/100	CG2.5M5		M5	21	9.1	1.1	12	8	2.5	2	1	1	-	-	-	-
UTIH1437/100	CG2.5M6		M6	26	10	0.9	15	9	2.5	2	2	1	-	-	-	-
UTIH1437A/100	CG2.5M8		M8	26	10	0.9	15	9	2.5	2	2	1	-	-	-	-
UTIH1403S/100	CG4SM5	4 7/0.85	M5	21	9	1.5	11	8.0	3.3	2	1	1	-	-	-	-
UTIH1403L/100	CG4LM5		M5	27	9	1.5	15	9	3.3	2	2	1	-	-	-	-
UTIH1404/100	CG4M6		M6	28	10	1.2	15	9	3.3	2	2	1	-	-	-	-
UTIH1404A/100	CG4M8		M8	29	13	1.0	13	9	3.3	2	2	1	-	-	-	-
UTIH1404B/100	CG4M10		M10	29	13	1.0	16	9	3.3	2	2	1	-	-	-	-
UTIH1405/100	CG6M6	6 7/1.04	M6	27	10	1.2	15	9	3.7	-	2	1	-	1	1	4.4
UTIH1405A/100	CG6M8		M8	29	14	0.9	17	9	3.7	-	2	1	-	1	1	
UTIH1405B/100	CG6M10		M10	29	14	0.9	17	9	3.7	-	2	1	-	1	1	
UTIH1406S/50	CG10SM6	10 7/1.35	M6	27	12	1.8	16	9	4.7	-	2	1	-	1	1	5.7
UTIH1406L/50	CG10LM6		M6	29	12	1.8	16	12	4.7	-	2	2	-	1	1	
UTIH1406A/50	CG10M8		M8	29	14	1.6	16	9	4.7	-	2	1	-	1	1	
UTIH1406B/50	CG10M10		M10	31	14	1.6	16	9	4.7	-	2	1	-	1	1	
UTICG10M12/50	CG10M12		M12	33	17	1.4	20	11	4.7	-	2	1	-	1	1	
UTIH1407A/50	CG16M5	16 7/1.70	M5	40	12	2.3	16	21	5.5	-	-	3	2	2	1	6.3
UTIH1407/50	CG16M6		M6	40	12	2.3	16	21	5.5	-	-	3	2	2	1	
UTIH1408/50	CG16M8		M8	40	14	1.9	16	21	5.5	-	-	3	2	2	1	
UTIH1408A/50	CG16M10		M10	42	14	1.9	19	21	5.5	-	-	3	2	2	1	
UTIH1445/50	CG16M11		M11	44	17	2.8	19	22	5.5	-	-	-	2	2	1	
UTICG16M12/50	CG16M12		M12	46	17	1.4	21	19	5.5	-	-	3	2	2	1	
UTIH1409/100	CG20M6	20 19/0.44	M6	35	13	2.3	14	19	6.3	-	-	-	2	-	1	7.0
UTIH1410/100	CG20M8		M8	42	14	2.2	19	20	6.3	-	-	-	2	-	1	
UTIH1411/100	CG20M10		M10	42	14	2.0	19	20	6.3	-	-	-	2	-	1	
UTIH1411A/100	CG20M12		M11	42	15	1.9	19	20	6.3	-	-	-	2	-	1	
UTIH1415A/50	CG25M6	25 19/1.35	M6	44	17	2.2	19	22	7.1	-	-	-	2	2	1	7.7
UTIH1415/50	CG25M8		M8	44	17	2.2	19	22	7.1	-	-	-	2	2	1	
UTIH1416/50	CG25M10		M10	44	17	1.9	19	22	7.1	-	-	-	2	2	1	
UTIH1416A/50	CG25M11		M11	44	17	1.9	19	22	7.1	-	-	-	2	2	1	
UTIH1416B/50	CG25M12		M12	51	18	1.7	25	21	7.1	-	-	-	2	2	1	
UTIH1365/50	CG35M6	35 19/1.53	M6	44	18	2.7	19	22	8.4				2	2	1	9.2
UTIH1366/50	CG35M8		M8	44	18	2.7	19	22	8.4				2	2	1	
UTIH1368/50	CG35M10		M10	44	18	2.7	19	22	8.4				2	2	1	
UTIH1369/50	CG35M12		M12	51	20	2.4	25	22	8.4				2	2	1	
UTIH1442/25	CG35M11	38 7/0.104	M11	51	19	3.7	27	22	8.7				2	2	1	10.4
UTIH1419/25	CG50M8	50 19/1.78	M8	51	18	3.1	27	22	9.5				2	2	1	10.4
UTIH1420/25	CG50M10		M10	51	19	3	27	22	9.5				2	2	1	
UTIH1421/25	CG50M12		M12	51	21	2.8	27	22	9.5				2	2	1	

Copper Lug Sizes 16mm² and above are available in single pieces.

Proudly Distributed By



1300 555 586

www.repelec.com.au

Sign up or log in to repelec.com.au

Facebook Instagram Twitter YouTube @RepelecAU

Page 2