



## Quick Overview

---

Utilux Copper Crimp Links

## Features

---

### Utilux Copper Crimp Links

- Solid drawn copper tube
- Centre dimples
- Ends reamed

## Details

---

Part No.	UTIH1460/25
Brand	Utilux
Pack Quantity	25
Unit Of Measure	Box
Compendium Page #	317

## Additional Information

Part No.	Description	Conductor Area (mm <sup>2</sup> )	Stranding Metric	Dimensions (mm)		No. of Crimps (Tool No.)						
				A	I.D.	00	18	20	21	22	38A	4
UTIH1451/100	CK0.5	0.5	1/0.80	22	2.1	2	-	-	-	-	-	-
UTIH1467/100	CK02.5	2.5	7/0.67	22	2.5	2	-	-	-	-	-	-
UTIH1452/50	CK4	4	7/0.85	22	3.3	2	1	-	-	-	-	-
UTIH1453/50	CK6	6	7/1.04	22	3.7	2	1	-	2	2	1	-
UTIH1454/50	CK10	10	7/1.35	22	4.7	2	1	-	2	2	1	-
UTIH1455/50	CK16	16	7/1.70	44	5.5	-	3	2	2	2	1	-
UTIH1456/50	CK20	20	19/0.44	44	6.3	-	-	2	2	2	1	-
UTIH1458/50	CK25	25	19/1.35	48	7.1	-	-	2	2	2	1	-
UTIH1488/25	CK35	35	19/1.53	48	8.4	-	-	2	2	2	1	-
UTIH1460/25	CK50	50	19/1.78	48	9.5	-	-	2	2	2	1	-
UTIH1461/20	CK70	70	19/2.14	51	11.0	-	-	2	-	2	1	-
UTIH1462/20 UTIH1462/1	CK95	95	37/1.78	54	13.4	-	-	2	-	2	1	-
UTIH1492/20 UTIH1492/1	CK120	120	37/2.03	65	15.5	-	-	-	-	2	1	-
UTIH1493/20* UTIH1493/1*	CK150	150	37/2.25	65	16.3	-	-	-	-	-	2	-
UTIH1494/1	CK185	185	37/2.52	65	18.4	-	-	-	-	-	2	-
UTIH1495/1	CK240	240	61/2.25	89	21.2	-	-	-	-	-	3	-
UTIH1496/1	CK300	300	61.2.52	89	23.8	-	-	-	-	-	3	-
UTIH1470/1	CK400	400	61/2.85	89	26.8	-	-	-	-	-	-	-
UTIH1471/1	CK500	500	61/3.20	114	30.0	-	-	-	-	-	-	-
UTIH1499/1*	CK630	630	127/2.52	114	33.5	-	-	-	-	-	-	-
UTIH1474/1	CK800	800	127/2.85	230	39.3	-	-	-	-	-	-	-
UTIH1475/1	CK1000	1000	127/3.20	230	43.8	-	-	-	-	-	-	-

\* All sizes of crimp links are compatible with imperial size cables except those marked\*

Proudly Distributed By



1300 555 586

www.repelec.com.au

Sign up or log in to repelec.com.au

Facebook Instagram X YouTube @RepelecAU

Page 2