

LINK, CU, 95mm2 CENTRE DIMPLE CK95 20



Quick Overview

Utilux Copper Crimp Links Centre Dimple CK95 95mm² (Pack of 20)

Features

Features & Benefits

- Solid drawn copper tube
- · Centre dimples
- · Ends reamed

Details

Part No.	UTIH1462/20
Brand	Utilux
Pack Quantity	20
Unit Of Measure	Box
Compendium Page #	317














Part No.		Conductor Area (mm²)	Stranding Metric	Dime							
	Description			(mm) A I.D.		00	No. 18	of Crim 20 21			ool No.) 38A 4
UTIH1451/100	CK0.5	0.5	1/0.80	22	2.1	2	-	8-	17.	7	(-
UTIH1467/100	CK02.5	2.5	7/0.67	22	2.5	2	_	2	(2)	<u>u</u>	12
UTIH1452/50	CK4	4	7/0.85	22	3.3	2	1	(-)	-	-	-
UTIH1453/50	CK6	6	7/1.04	22	3.7	2	1	1.7	2	2	1
UTIH1454/50	CK10	10	7/1.35	22	4.7	2	1	-	2	2	1
UTIH1455/50	CK16	16	7/1.70	44	5.5	:-:	3	2	2	2	1
UTIH1456/50	CK20	20	19/.044	44	6.3	×7.	7	2	2	2	1
UTIH1458/50	CK25	25	19/1.35	48	7.1	12	_	2	2	2	1
UTIH1488/25	CK35	35	19/1.53	48	8.4	-	7	2	2	2	1
UTIH1460/25	CK50	50	19/1.78	48	9.5	100	2	2	2	2	1
UTIH1461/20	CK70	70	19/2.14	51	11.0	-	-	2	-	2	1
UTIH1462/20 UTIH1462/1	CK95	95	37/1.78	54	13.4	12	-	2	_	2	1
UTIH1492/20 UTIH1492/1	OK120	120	37/2.03	65	15.5	-	ē	::7:	-	2	1
UПН1493/20* UПН1493/1*	OK150	150	37/2.25	65	16.3	-	-	-	-	-	2
UTIH1494/1	CK185	185	37/2.52	65	18.4	-	-	-	-	-	2
UTIH1495/1	CK240	240	61/2.25	89	21.2	12	2	12	121	2	3
UTIH1496/1	CK300	300	61.2.52	89	23.8		៊		:7:	5	3
UTIH1470/1	CK400	400	61/2.85	89	26.8	-	-	-	-	-	-
UTIH1471/1	CK500	500	61/3.20	114	30.0	-	-	-	-	-	-
UTIH1499/1*	CK630	630	127/2.52	114	33.5	823	2	12	121	2	(2)
UTIH1474/1	CK800	800	127/2.85	230	39.3		-	1. 1	-	-	-
UTIH1475/1	CK1000	1000	127/3.20	230	43.8	12	_	(2)	121	2	(2)

^{*} All sizes of crimp links are compatible with imperial size cables except those marked*





1300 555 586





