

Quick Overview

Utilux Heavy Duty Pre-Insulated Ring Terminals



Features

Utilux Heavy Duty Pre-Insulated Ring Terminals

- Seamless drawn copper tube electro tinned, black nylon insulator
- Palms radiused

Details

Part No.	UTIH2003S/100
Brand	Utilux
Pack Quantity	100
Unit Of Measure	Box
Compendium Page #	335

Additional Information

Part No.	Descript.	Terminal Size	Conductor Area mm ²	Stud Size	Dimensions mm					Max. Insul. Dia. mm
					A	B	C	E	F	
UTIH2001S/100	RHD0.5M5S	0.5	1/0.80	M5	26.0	8.6	0.9	11.1	12.7	3.5
UTIH2001L/100	RHD0.5M5L			M5	29.4	8.7	0.9	15.1	12.7	
UTIH2002/100	RHD0.5M6			M6	30.0	10.3	0.8	15.1	12.7	
UTIH2036/100	RHD2.5M5	2.5	7/0.67	M5	26.2	9.0	1.0	11.9	12.7	4.3
UTIH2037/100	RHD2.5M6			M6	30.9	10.3	0.9	15.1	12.7	
UTIH2003S/100	RHD4M5S	4.0	7/0.85	M5	28.9	8.7	1.5	11.1	14.0	6.1
UTIH2003L/100	RHD4M5L			M5	32.6	8.7	1.4	14.7	14.0	
UTIH2004/100	RHD4M6			M6	32.0	10.0	1.2	15.1	14.0	
UTIH2005/100	RHD6M6	6	7/1.04	M6	31.0	10.0	1.2	15.1	13.0	6.8
UTIH2006/100	RHD10M6	10	7/1.35	M6	31.8	11.9	1.8	15.1	13.0	8.3

