

Quick Overview

Utilux High Temperature Uninsulated Ring Terminals



Features

Utilux High Temperature Uninsulated Ring Terminals

- Rated at 280°C
- Nickel plated

Details

Part No.	UTIH3225/100
Brand	Utilux
Pack Quantity	100
Unit Of Measure	Pack
Compendium Page #	335

Additional Information

Part No.	Descript.	Terminal Size	Conductor Area mm ²	Stud Size	Dimensions mm					Max. Insulated Dia. mm
					A	B	C	E	F	
UTIH3215/100	RHT1.5M5	No.1 22-16AWG	0.5 to 1.5	M5	19.2	7.9	0.7	7.9	9.0	3.6
UTIH3223/100	RHT2.5M4	No.2 16-14AWG	1.5 to 2.5	M4	22.5	8.7	0.7	8.7	11.1	4.3
UTIH3225/100	RHT2.5M5			M5	22.5	8.7	0.7	8.7	11.1	
UTIH3227/100	RHT2.5M6			M6	27.8	12.7	0.7	12.7	11.1	
UTIH3233/100	RHT6M5	No.3 12-10AWG	2.5 to 6.0	M5	24.4	9.5	0.9	9.5	12.7	6.1
UTIH3234/100	RHT6M6			M6	29.3	12.7	0.9	12.7	12.7	

