

Quick Overview

Utilux Supergrip Ring Terminals



Features

Utilux Supergrip Ring Terminals

- Fitted with a copper ferrule and pre-insulated for secure insulation support
- Copper electro tinned to minimise corrosion
- Serrated barrel provides secure mechanical and electrical connection

Details

Part No.	UTIH4223/100
Brand	Utilux
Pack Quantity	100
Unit Of Measure	Pack
Compendium Page #	334

Additional Information

Part No.	Descript.	Terminal Size	Conductor Area mm ²	Stud Size	A	B	Dimension C
UTIH4211/100	RRSGM3S	NO.1 RED 22-16AWG	0.5 TO 1.5	M3	18.0	5.5	0.7
UTIH4216/100	RRSGM3M			M3	19.9	6.6	0.7
UTIH4212/100	RRSGM3L			M3	21.3	8.0	0.7
UTIH4213/100	RRSGM4S			M4	19.9	6.6	0.7
UTIH4214/100	RRSGM4L			M4	21.3	8.0	0.7
UTIH4215/100	RRSGM5S			M5	21.3	8.0	0.7
UTIH4217/100	RRSGM5L			M5	27.3	11.6	0.7
UTIH4218/100	RRSGM6			M6	27.3	11.6	0.7
UTIH4219/100	RRSGM8			M8	27.3	11.6	0.7
UTIH4240/100	RRSGM10			M10	31.0	13.6	0.7
UTIH4220/100	BRSGM3S	NO.2 BLUE 16-14AWG	1.5 TO 2.5	M3	19.9	6.6	0.8
UTIH4221/100	BRSGM3L			M3	22.3	8.5	0.8
UTIH4222/100	BRSGM4S			M4	19.9	6.6	0.8
UTIH4223/100	BRSGM4L			M4	22.3	8.5	0.8
UTIH4225/100	BRSGM5S			M5	22.3	8.5	0.8
UTIH4226/100	BRSGM5L			M5	22.3	9.5	0.8
UTIH4227/100	BRSGM6			M6	27.3	12.0	0.8
UTIH4228/100	BRSGM8			M8	27.3	12.0	0.8
UTIH4229/100	BRSGM10			M10	31.0	13.6	0.8
UTIH4232/50	YRSGM3	NO.3 YELLOW 12-10AWG	2.5 TO 6.0	M3	23.2	7.2	1.0
UTIH4230/50	YRSGM4S			M4	23.2	7.2	1.0
UTIH4231/50	YRSGM4L			M4	27.1	9.5	1.0
UTIH4233/50	YRSGM5			M5	27.1	9.5	1.0
UTIH4234/50	YRSGM6			M6	30.0	12.0	1.0
UTIH4237/50	YRSGM8			M8	34.5	15.0	1.0
UTIH4238/50	YRSGM10			M10	34.5	15.0	1.0
UTIH4239/30	YRSGM12			M12	39.1	19.2	1.0

Proudly Distributed By



☎ 1300 555 586

🌐 www.repelec.com.au

✍ Sign up or log in to repelec.com.au

📱 📺 📷 📺 @RepelecAU

Page 2