

# ANACONDA FLEXIBLE METAL CONDUIT & FITTINGS



APPROVALS: AUS Ex 04.3900X DIP A21 IP66/68

## PROVIDES SUPERIOR HEAT, OIL, CHEMICAL AND WEATHER RESISTANCE ANACONDA 'AEF RANGE' CONDUIT

Size (mm)	Part No.	Inside Dia. (mm)	Approx Inside Bend Dia. (mm)	Length (m)	ANACONDA FITTINGS		
					Straight	45°	90°
10	AEF14	6.3	88.9	15	-	-	-
12	AEF516	10	101.6	15	-	-	-
16	AEF38	12	101.6	15/30/240	C16/M16	C16/M16/45A	C16/M16/90A
16	AEF38	12	101.6	15/30/240	C16/M20	C16/M20/45A	C16/M20/90A
20	AEF12	16	127.0	15/30/150	C20/M20	C20/M20/45A	C20/M20/90A
25	AEF34	21	152.4	15/30/120	C25/M25	C25/M25/45A	C25/M25/90A
32	AEF100	26	203.2	15/30/120	C32/M32	C32/M32/45A	C32/M32/90A
40	AEF114	35	228.6	15/60	C40/M40	C40/M40/45A	C40/M40/90A
50	AEF112	40	279.4	15	C50/M50	C50/M50/45A	C50/M50/90A
63	AEF200	51.5	355.6	15	C63/M63	C63/M63/45A	C63/M63/90A
83	AEF212	63	482.6	15	-	-	-
95	AEF300*	78	762.0	7.62	-	-	-
115	AEF312*	90	812.8	7.62	-	-	-
128	AEF400*	102	863.6	7.62	-	-	-
137	AEF500*	126	1117.6	7.62	-	-	-
170	AEF600*	153	1524.0	7.62	-	-	-

NOTE: To order different roll lengths, add appropriate length amount after Part No. (eg: AEF38-15 to order in 15m lengths)

\* No need to add roll length amount after part no.



APPROVALS: AUS Ex 04.3900X DIP A21 IP66/68

## SUPERIOR LIQUID-TIGHT RACEWAY FOR WIRING WHERE EXTREME TEMPERATURES APPLY ANACONDA 'HCX RANGE' CONDUIT

Size (mm)	Part No.	Inside Dia. (mm)	Approx Inside Bend Dia. (mm)	Length (m)	ANACONDA FITTINGS		
					Straight	45°	90°
16	HCX38	12	101.6	30/150	C16/M16	C16/M16/45A	C16/M16/90A
16	HCX38	12	101.6	30/150	C16/M20	C16/M20/45A	C16/M20/90A
20	HCX12	16	127.0	30/150	C20/M20	C20/M20/45A	C20/M20/90A
25	HCX34	21	152.4	30/150	C25/M25	C25/M25/45A	C25/M25/90A
32	HCX100	26	203.2	30	C32/M32	C32/M32/45A	C32/M32/90A
40	HCX114	35	228.6	15	C40/M40	C40/M40/45A	C40/M40/90A
50	HCX112	40	279.4	15	C50/M50	C50/M50/45A	C50/M50/90A
63	HCX200	51.5	355.6	15	C63/M63	C63/M63/45A	C63/M63/90A
95	HCX300*	78	762.0	7.62	-	-	-
128	HCX400*	102	863.6	7.62	-	-	-

NOTE: To order different roll lengths, add appropriate length amount after Part No. (eg: HCX38-30 to order in 30m lengths)

\* No need to add roll length amount after part no.