

Locfit Data Sheet

WMIS Locfit Galvanized AS/NZ1397- Conduits are manufactured from BHP in line galvanized steel tube. It has an accurate circular cross section, a uniform wall thickness and continuously welded seams. The interior and exterior surfaces are thoroughly and evenly coated with zinc via the inline process.

WMIS Locfit Conduit can be supplied in a Hot Dipped Galvanized finish, Galvanizing is carried out to Australian Standard 4680-2006, and ZM 275 (Maxi)

The conduit comes in standard 4 meter lengths up to 50mm and 3 or 6 meters for larger sizes, all Conduits include 1 coupling per length, as per Australian Standard specification 2053.7.

Storage: It is highly recommended that Steel Conduit be stored in a dry area until used.

Application: WMIS Conduit can be installed indoors or outdoors, in dry or wet locations, exposed or concealed, in all kinds of atmospheric conditions, and in hazardous locations. It provides excellent mechanical protection for the conductors while reducing Electro-Magnetic field exposure and shielding against Electro-Magnetic Interference.

Part	Conduit	Outside	Inside	Wall
No:	Size:	Diameter:	Diameter:	Thickness:
WMI-20LF-A	20mm	20mm	16.8mm	1.2 mm
WMI-25LF-A	25mm	25mm	21.4mm	1.2mm
WMI-32LF-A	32mm	32mm	28.4mm	1.2mm
WMI-40LF-A	40mm	40mm	36.4mm	1.2mm
WMI-50LF-A	50mm	50mm	46.0mm	1.2mm
WMI-63LF-A	63mm	63.5mm	59.9mm	1.2mm
WMI-100LF-A	101mm	101mm	97.0mm	2.0mm