

[Home](#) > [Low Voltage Power Distribution](#) > [Circuit Breakers](#) > [Moulded Case Circuit Breakers](#) > [Series G](#) > [GE - Frame](#) > [MCCBs 25kA Range](#)

Quick Links

[Products Overview](#)

[Product Catalogues](#)

[About Us](#)

[PowerChain Management Solutions](#)

[Services & Support](#)

[Handles Hotline](#)

Agency Products

[Kyoritsu](#)

[Circutor](#)

[ETA](#)

[M. Schneider](#)

[Elsta](#)

[Marechal](#)



GE - Frame Moulded Case Circuit Breakers MCCBs 25kA Range

More Info

[GE Frame Product Summary](#)

[GE Frame Product Literature](#)


[MCCBs 18kA Range](#)

[MCCBs 25kA Range](#)

[MCCBs 40kA Range](#)

[MCCBs 70kA Range](#)

[Auxiliaries and Accessories](#)

MCCB Description		25kA Range		
Poles		1 Pole	3 Pole	4 Pole (TPSN)
Utilisation Category		A	A	A
Impulse Withstand Voltage		6kV	6kV	6kV
Thermal Trip		Fixed	Fixed	Fixed
Magnetic Trip		16A to 40A fixed at 500A Others fixed at 10xIn	16A to 40A fixed at 500A Others fixed at 10xIn	16A to 40A fixed at 500A Others fixed at 10xIn
Breaking Capacity IEC 60947-2 / BS EN 60947-2 (AC 50/60Hz)				
380V AC/	Icu (kA)	25	25	25
415V AC	Ics (kA)	13	13	13
220V AC/	Icu (kA)	35	35	35
240V AC	Ics (kA)	18	18	18
250V DC	Icu (kA)	-	25	25
	Ics (kA)	-	13	13
Current Rating (A)		1 Pole	3 Pole	4 Pole (TPSN)
MCCBs		List No.	List No.	List No.
Current Rating (A)				
16A		GEE1016FFG	GEE3016FFG	GEE4016FFG
20A		GEE1020FFG	GEE3020FFG	GEE4020FFG
32A		GEE1032FFG	GEE3032FFG	GEE4032FFG
40A		GEE1040FFG	GEE3040FFG	GEE4040FFG
50A		GEE1050FFG	GEE3050FFG	GEE4050FFG
63A		GEE1063FFG	GEE3063FFG	GEE4063FFG
80A		GEE1080FFG	GEE3080FFG	GEE4080FFG
100A		GEE1100FFG	GEE3100FFG	GEE4100FFG
125A		GEE1125FFG	GEE3125FFG	GEE4125FFG
Current Rating (A)		1 Pole	3 Pole	4 Pole (TPSN)
Circuit Breaker Switches with high magnetic trip above 1700A		List No.	List No.	List No.
Current Rating (A)				
100A		-	GEK3100KSG	GEK4100KSG
125A		-	GEK3125KSG	GEK4125KSG
160A		-	GEK3160KSG	GEK4160KSG
Terminal Capacities (max.)		70mm ²	70mm ² *	70mm ² *
Dimensions (mm)				
	A	25.4	76.2	101.6
	B	140	140	140
	C	70.4	70.4	70.4
	D	92	92	92
Weight (kg) approx.		0.5	1.4	1.8