



Datasheet



Weatherproof LED Exit Sign - IP65

CAT NO. 684650, 684651, 684652, 684654, 684655, 684656, 684657, 684658, 684659, 684660, 684661, 684662, 684664, 684670, 684671, 684672, 684674, 684681, 684682, 684684, 684689



Mode of operation	Maintained
Supply voltage	240V a.c. (+/- 6%) 50 Hz
Power consumption	5.4W
Batteries	2X2 Sub-C NiCad
Operating temperature	10°C to 40°C
IP rating	IP65
Impact rating	IK-08
Compliance	AS/NZS 2293 AS/NZS 60598  

Weatherproof LED Exit Sign - IP65

CAT NO. **684650, 684651, 684652, 684654, 684655, 684656, 684657, 684658, 684659, 684660, 684661, 684662, 684664, 684670, 684671, 684672, 684674, 684681, 684682, 684684, 684689**

Product codes and barcodes	
Catalogue Numbers	Description
24m	
684650	WP LED 2X1W Exit sml IP65 RM
684651	WP LED 2X1W Exit sml IP65 RML
684652	WP LED 2X1W Exit sml IP65 RMR
684654	WP LED 2X1W Exit sml IP65 'EXIT'
684655	WP LED 2X1W Exit sml IP65 'EXIT' left
684656	WP LED 2X1W Exit sml IP65 'EXIT' right
684657	WP LED 2X1W Exit sml IP65 'EXIT' left/right
684660	Axiom WP LED 2X1W Exit sml IP65 RM
684661	Axiom WP LED 2X1W Exit sml IP65 RML
684662	Axiom WP LED 2X1W Exit sml IP65 RMR
684664	Axiom WP LED 2X1W Exit sml IP65 'EXIT'
32m	
684670	WP LED 2X1W Exit lrg IP65 RM
684671	WP LED 2X1W Exit lrg IP65 RML
684672	WP LED 2X1W Exit lrg IP65 RMR
684674	WP LED 2X1W Exit lrg IP65 'EXIT'
684680	Axiom WP LED 2X1W Exit lrg IP65 RM
684681	Axiom WP LED 2X1W Exit lrg IP65 RML
684682	Axiom WP LED 2X1W Exit lrg IP65 RMR
684684	Axiom WP LED 2X1W Exit lrg IP65 'EXIT'
Replacement part No.	
684689	Battery pack 2X2 SubC

Accessories	
684690	Wall bracket for 24m
684691	Side bracket for 24m
684692	Ceiling bracket for 24m

Classification	
24m	C0: E2.5 C90:E2
32m	C0: E2.5 C90:E2

RM = Running man straight

RML = Running man left

RMR = Running man right

- Low energy consumption - save up to 70% on energy consumption*
- Two sizes: 24m and 32m viewing distance
- Long life LED light source - up to 50,000 hours
- Weatherproof enclosure IP65
- High resistance polycarbonate ABS clear cover
- Includes age and oil resistant soft rubber gasket
- Removable gear tray for ease of maintenance and installation
- Two-rate charge mechanism
- High temperature NiCad batteries
- Stand alone and Axiom versions available
- Large terminal block for ease of connection
- Low cost maintenance
- Manufactured in Australia

* When compared to conventional fluorescent solutions.

Legrand Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.